

Features

- 2x 10" bass reflex design combined with 4"/2.5" coaxial compression driver
- Extended low frequency response at reduced power
- Integrated rigging system for use with L-series modules
- 2x NLT4 2x NL8 on the rear
- 4x ergonomic handles, 2x on the rear, 1x on the left, 1x on the right
- All Quint Audio loudspeakers are designed for use in combination with Quint Audio processors & amplifiers
- All Quint Audio loudspeaker presets are matched in level and phase at the crossover frequency for easy mix & match
- Factory system presets available



Applications

- Line Source

Construction

- Birch plywood enclosure
- Durable hybrid coating, resistant to wear, impact, and weathering
- Klotz internal wiring
- Neutrik speakON® connectors
- Powder coated steel grille with acoustically transparent fabric on the back

model	L20
filter	2-channel DSP control
loudspeaker components	2x10"/4"/2.5"
impedance	5 Ohm
peak SPL* / freq. range (-6dB)	140.5dB/80Hz-20kHz
max SPL* / freq. range (-6dB)	123dB/80Hz-20kHz
max SPL -10dB / freq. range (-6dB)	113dB/40Hz-20kHz
max SPL -20dB / freq. range (-6dB)	103dB/35Hz-20kHz
dispersion (HxV)	110°x12°
connections	2x 8-pole speakON 2x 4-pole speakON
weight	32kg
size (wxhxd)	840 x 270 x 450mm

* Measurements are conform to AES75 and carried out with P9 processor and A4 amplifier. Values are scaled to 1m free field.

Accessories

