

B10

Compact sub for touring & installation

Features

- 10" bass reflex design
- Maintained low frequency performance at full power
- Stackable in omni & cardioid setup
- Mounting points for fixed installation
- 2x NLT4 on the rear
- M20 pole mount on top
- 1x ergonomic handle on the back
- Rubber feet for stability on the bottom
- All Quint Audio loudspeakers are designed for use in combination with Quint Audio processors & amplifiers
- All Quint Audio loudspeaker presets are matched in level and phase at the crossover frequency for easy mix & match
- Factory system presets available



Applications

- Subwoofer for compact systems

Construction

- Birch plywood enclosure
- Durable hybrid coating, resistant to wear, impact, and weathering
- Klotz internal wiring
- Neutrik speakON® connectors
- Powder coated steel grille with acoustically transparent fabric on the back

Model	B10
Filter	1-channel DSP control
Loudspeaker components	10"
Impedance	4 Ohm
Peak SPL* / Freq. range (-6db)	122.5dB / 33Hz-100Hz
Max SPL* / Freq. range (-6db)	111dB / 33Hz-100Hz
Max SPL -10db / Freq. range (-6db)	N/A
Max SPL -20db / Freq. range (-6db)	N/A
Dispersion (HxV)	Omni
Connections	2x 4-pole speakON
Weight	17kg
Size (WxHxD)	450 x 275 x 450mm

* Measurements are conform to AES75 and carried out with P9 processor and A42 amplifier. Values are scaled to 1m free field.

Accessories

