

C15

Full range fixed curvature module for installation

Features

- 15" bass reflex design combined with 4"/2.5" coaxial compression driver
- Maintained low frequency performance at full power
- Mounting points for fixed installation
- 2x NLT4 on the rear
- All Quint Audio loudspeakers are designed for use in combination with Quint Audio processors & amplifiers
- All Quint Audio loudspeaker presets are matched in level and phase at the crossover frequency for easy mix & match
- Factory system presets available

Applications

- Full range line source

Construction

- Birch plywood enclosure
- Durable hybrid coating, resistant to wear, impact, and weathering
- Klotz internal wiring
- Neutrik speakON® connectors
- Powder coated steel grilles with acoustically transparent fabric on the back



Model	C15
Filter	2-channel DSP control
Loudspeaker components	15"/4"/2.5"
Impedance	8 Ohm
Peak SPL* / Freq. range (-6db)	138dB / 33Hz-20kHz
Max SPL* / Freq. range (-6db)	120dB / 33Hz-20kHz
Max SPL -10db / Freq. range (-6db)	N/A
Max SPL -20db / Freq. range (-6db)	N/A
Dispersion (HxV)	90°x20°
Connections	2x 4-pole speakON
Weight	39kg
Size (WxHxD)	730 x 425 x 515mm

* Measurements are conform to AES75 and carried out with P9 processor and A42 amplifier. Values are scaled to 1m free field.

Accessories

