

C30

High performance full range active noise cancelling point source for installation

Features

- 4x 15" bass reflex design combined with 4"/2.5" coaxial compression driver
- Symmetrical design
- Maintained low frequency performance at full power noise suppression outside the sound field
- Mounting points for fixed installation
- 2x NLT4 on the rear

All Quint Audio loudspeakers are designed for use in combination with Quint Audio processors & amplifiers

- All Quint Audio loudspeaker presets are matched in level and phase at the crossover frequency for easy mix & match
- Factory system presets available



Applications

- Stand alone full range loudspeaker



Construction

- Birch plywood enclosure
- Durable hybrid coating, resistant to wear, impact, and weathering
- Klotz internal wiring
- Neutrik speakON® connectors
- Powder coated steel grilles with acoustically transparent fabric on the back

Model	C30
Filter	3-channel DSP control
Loudspeaker components	4x15"/4"/2.5"
Impedance	4 Ohm
Peak SPL* / Freq. range (-6db)	145dB / 43Hz-20kHz
Max SPL* / Freq. range (-6db)	130.5dB / 43Hz-20kHz
Max SPL -10db / Freq. range (-6db)	N/A
Max SPL -20db / Freq. range (-6db)	N/A
Dispersion (HxV)	70° x 40°
Connections	2x 8-pole speakON
Weight	86kg
Size (WxHxD)	900 x 490 x 830mm


* Measurements are conform to AES75 and carried out with P9 processor and A42 amplifier. Values are scaled to 1m free field.

Accessories




C30-H1

C30-B1



C15-E2



C15-E1

