

C36

High performance active directivity control full range fixed curvature module for installation

Features

- 2x 18"/2x 15" bass reflex 4x 8" closed box design combine with 2x 4"/2.5" coaxial compression driver
- Symmetrical design
- Maintained low frequency performance at full power
- Noise suppression outside the sound field
- Optional touring rigging
- Mounting points for fixed installation
- 2x NL8 on the rear
- Truck size cabinet for efficient transportation
- All Quint Audio loudspeakers are designed for use in combination with Quint Audio processors & amplifiers
- All Quint Audio loudspeaker presets are matched in level and phase at the crossover frequency for easy mix & match
- Factory system presets available



Applications

- Full range line source

Construction

- Birch plywood enclosure
- Durable hybrid coating, resistant to wear, impact, and weathering
- Klotz internal wiring
- Neutrik speakON® connectors
- Powder coated steel grilles with acoustically transparent fabric on the back

Model	C36
Filter	4-channel DSP control
Loudspeaker components	2x18"/2x15"/4x8"/2x4"/2x2.5"
Impedance	4 Ohm
Peak SPL* / Freq. range (-6db)	147dB / 33Hz-20kHz
Max SPL* / Freq. range (-6db)	129dB / 33Hz-20kHz
Max SPL -10db / Freq. range (-6db)	N/A
Max SPL -20db / Freq. range (-6db)	N/A
Dispersion (HxV)	N/A
Connections	110° x 10°
Weight	2x 8-pole speakON
Size (WxHxD)	140kg
	1180 x 540 x 1010mm

* Measurements are conform to AES75 and carried out with P9 processor and A42 amplifier. Values are scaled to 1m free field.

Accessories

