

Features

- 4" closed box design combined with 1" dome tweeter
- Coaxial design
- Extended low frequency response at reduced power
- Tool free mountable L-bracket
- Mounting points for fixed installation
- 2x phoenix connectors on the back
- 3/8" thread on bottom, M10 thread on top, M6 threads on left and right
- All Quint Audio loudspeakers are designed for use in combination with Quint Audio processors & amplifiers
- All Quint Audio loudspeaker presets are matched in level and phase at the crossover frequency for easy mix & match
- Factory system presets available

Applications

- Fill for larger systems

Construction


- Birch plywood enclosure
- Durable hybrid coating, resistant to wear, impact, and weathering
- Klotz internal wiring
- Neutrik speakON® connectors
- Powder coated steel grilles with acoustically transparent fabric on the back



Model	C4
Filter	1-channel DSP control
Loudspeaker components	4"/1"
Impedance	8 Ohm
Peak SPL* / Freq. range (-6db)	113dB / 140Hz-20kHz
Max SPL* / Freq. range (-6db)	95.5dB / 140Hz-20kHz
Max SPL -10db / Freq. range (-6db)	85.5dB / 140Hz-20kHz
Max SPL -20db / Freq. range (-6db)	75.5dB / 55Hz-20kHz
Dispersion (HxV)	100° conical
Connections	2x
Phoenix 2,5/ 2-ST-5,08	
Weight	2kg
Size (WxD)	125 x 125 x 125mm

* Measurements are conform to AES75 and carried out with P9 processor and A42 amplifier. Values are scaled to 1m free field.

Accessories



C4-H1

