

# C6

Compact point source for installation

## Features

- 6.5" bass reflex design combined with 1.7" compression driver
- Coaxial design
- Extended low frequency response at reduced power
- Integrated U-brackets for top and rear mounting
- 2x phoenix connectors on the back
- All Quint Audio loudspeakers are designed for use in combination with Quint Audio processors & amplifiers
- All Quint Audio loudspeaker presets are matched in level and phase at the crossover frequency for easy mix & match
- Factory system presets available

## Applications

- Fill for larger systems

## Construction


- Birch plywood enclosure
- Durable hybrid coating, resistant to wear, impact, and weathering
- Klotz internal wiring
- Neutrik speakON® connectors
- Powder coated steel grilles with acoustically transparent fabric on the back



Model	C6
Filter	1-channel DSP control
Loudspeaker components	6.5"/1.7"
Impedance	16 Ohm
Peak SPL* / Freq. range (-6db)	125.5dB / 100Hz-20kHz
Max SPL* / Freq. range (-6db)	107dB / 100Hz-20kHz
Max SPL -10db / Freq. range (-6db)	97dB / 65Hz-20kHz
Max SPL -20db / Freq. range (-6db)	87dB / 60Hz-20kHz
Dispersion (HxV)	80° conical
Connections	2x
Weight	Phoenix 2,5/ 2-ST-5,08
Size (WxD)	6kg
	235 x 270 x 200mm

\* Measurements are conform to AES75 and carried out with P9 processor and A42 amplifier. Values are scaled to 1m free field.

## Accessories



C5-H1

