

Features

- 10" bassreflex design combined with 2x 1.7" compression driver
- Extended low frequency response at reduced power
- Integrated rigging system for use with L-series modules
- 2x NLT4 2x NL8 on the rear
- 4x ergonomic handles, 2x on the rear, 1x on the left, 1x on the right
- Truck size cabinet for efficient transportation
- All Quint Audio loudspeakers are designed for use in combination with Quint Audio processors & amplifiers
- All Quint Audio loudspeaker presets are matched in level and phase at the crossover frequency for easy mix & match
- Factory system presets available



Applications

- Full range line source

Construction

- Birch plywood enclosure
- Durable hybrid coating, resistant to wear, impact, and weathering
- Klotz internal wiring
- Neutrik speakON® connectors
- Powder coated steel grille with acoustically transparent fabric on the back

Model	L10
Filter	2-channel DSP control
Loudspeaker components	10"/2x1.7"
Impedance	10 Ohm
Peak SPL* / Freq. range (-6db)	133.5dB/100Hz-20kHz
Max SPL* / Freq. range (-6db)	117dB/100Hz-20kHz
Max SPL -10db / Freq. range (-6db)	107dB/40Hz-20kHz
Max SPL -20db / Freq. range (-6db)	97dB/35Hz-20kHz
Dispersion (HxV)	80° x 12°
Connections	2x 8-pole speakON 2x 4-pole speakON
Weight	21kg
Size (WxHxD)	580 x 270 x 450mm

* Measurements are conform to AES75 and carried out with P9 processor and A42 amplifier. Values are scaled to 1m free field.

Accessories

