

# M14

High performance full range monitor for touring

## Features

- 13.5" bass reflex design combined with 3" compression driver
- Coaxial design
- Maintained low frequency performance at full power
- Monitor angle(s) 30 degrees and 60 degrees
- Tool free mountable U-bracket
- 2x NL4 on the front, 2x NL4 on the left, 2x NL4 on the right
- 2x ergonomic handles, 1x on the left, 1x on the right
- Rubber feet for stability on the bottom
- All Quint Audio loudspeakers are designed for use in combination with Quint Audio processors & amplifiers
- All Quint Audio loudspeaker presets are matched in level and phase at the crossover frequency for easy mix & match
- Factory system presets available



## Applications

- Stand alone full range loudspeaker
- Live monitoring

## Construction

- Birch plywood enclosure
- Durable hybrid coating, resistant to wear, impact, and weathering
- Klotz internal wiring
- Neutrik speakON® connectors
- Powder coated steel grille with acoustically transparent fabric on the back

Model	M14
Filter	1/2-channel DSP control
Loudspeaker components	13.5"/3"
Impedance	8 Ohm
Peak SPL* / Freq. range (-6db)	134dB / 59Hz-16kHz
Max SPL* / Freq. range (-6db)	116dB / 59Hz-16kHz
Max SPL -10db / Freq. range (-6db)	N/A
Max SPL -20db / Freq. range (-6db)	N/A
Dispersion (HxV)	80° conical
Connections	6x 4-pole speakON
Weight	16kg
Size (WxHxD)	425 x 300 x 445mm

\* Measurements are conform to AES75 and carried out with P9 processor and A42 amplifier. Values are scaled to 1m free field.

## Accessories

