

## Features

- 12" bass reflex design combined with 5" air motion transformer
- Extended low frequency response at reduced power
- Tool free mountable U-bracket
- 2x NL4 on the rear
- 35mm Pole mount on bottom
- 1x ergonomic handle, 1x on the top
- Rubber feet for stability on the bottom and side
- All Quint Audio loudspeakers are designed for use in combination with Quint Audio processors & amplifiers
- All Quint Audio loudspeaker presets are matched in level and phase at the crossover frequency for easy mix & match
- Factory system presets available

## Applications

- Stand alone full range loudspeaker

## Construction

- Birch plywood enclosure
- Durable hybrid coating, resistant to wear, impact, and weathering
- Klotz internal wiring
- Neutrik speakON® connectors
- Powder coated steel grille with acoustically transparent fabric on the front



Model	T12
Filter	1-channel DSP control
Loudspeaker components	12"/5"
Impedance	8 Ohm
Peak SPL* / Freq. range (-6db)	131dB / 80Hz-20kHz
Max SPL* / Freq. range (-6db)	116dB / 80Hz-20kHz
Max SPL -10db / Freq. range (-6db)	106dB / 40Hz-20kHz
Max SPL -20db / Freq. range (-6db)	N/A
Dispersion (HxV)	80° x 20°
Connections	2x 4-pole speakON
Weight	26kg
Size (WxHxD)	360 x 610 x 415mm

\* Measurements are conform to AES75 and carried out with P9 processor and A42 amplifier. Values are scaled to 1m free field.

## Accessories

