

T15

Full range point source for touring

Features

- 15" bass reflex design combined with 3.5" compression driver
- Maintained low frequency performance at full power
- Quint Audio Quick Lock system on top
- Tool free mountable U-bracket
- 2x NLT4 on the rear
- 35mm Pole mount on bottom
- 3x ergonomic handles, 1x on the left, 1x on the right, 1x on the top
- Rubber feet for stability on the bottom
- All Quint Audio loudspeakers are designed for use in combination with Quint Audio processors & amplifiers
- All Quint Audio loudspeaker presets are matched in level and phase at the crossover frequency for easy mix & match
- Factory system presets available

Applications

- Stand alone full range loudspeaker

Construction

- Birch plywood enclosure
- Durable hybrid coating, resistant to wear, impact, and weathering
- Klotz internal wiring
- Neutrik speakON® connectors
- Powder coated steel grille with acoustically transparent fabric on the back



Model	T15
Filter	1-channel DSP control
Loudspeaker components	15"/3.5"
Impedance	8 Ohm
Peak SPL* / Freq. range (-6db)	137dB / 33Hz-20kHz
Max SPL* / Freq. range (-6db)	120dB / 33Hz-20kHz
Max SPL -10db / Freq. range (-6db)	N/A
Max SPL -20db / Freq. range (-6db)	N/A
Dispersion (HxV)	70° x 40°
Connections	2x 4-pole speakON
Weight	35kg
Size (WxHxD)	430 x 695 x 465mm

* Measurements are conform to AES75 and carried out with P9 processor and A42 amplifier. Values are scaled to 1m free field.

Accessories

