

# T16

High performance point source for touring

## Features

- 2x 8" bass reflex design combined with 3.5" compression driver
- Extended low frequency response at reduced power
- Quint Audio Quick Lock system on top and bottom
- Tool free mountable U-bracket
- 2x NLT4 on the rear
- 2x ergonomic handles, 1x on the left, 1x on the right
- Rubber feet for stability on the bottom
- All Quint Audio loudspeakers are designed for use in combination with Quint Audio processors & amplifiers
- All Quint Audio loudspeaker presets are matched in level and phase at the crossover frequency for easy mix & match
- Factory system presets available

## Applications

- Top loudspeaker in combination with a subwoofer

## Construction

- Birch plywood enclosure
- Durable hybrid coating, resistant to wear, impact, and weathering
- Klotz internal wiring
- Neutrik speakON® connectors
- Powder coated steel grille with acoustically transparent fabric on the back



Model	T16
Filter	1-channel DSP control
Loudspeaker components	2x8"/3.5"
Impedance	5 Ohm
Peak SPL* / Freq. range (-6db)	136.5dB / 100Hz-20kHz
Max SPL* / Freq. range (-6db)	122dB / 100Hz-20kHz
Max SPL -10db / Freq. range (-6db)	112dB / 70Hz-20kHz
Max SPL -20db / Freq. range (-6db)	102dB / 55Hz-20kHz
Dispersion (HxV)	110° x 40°
Connections	2x 4-pole speakON
Weight	25kg
Size (WxHxD)	295 x 570 x 335mm

\* Measurements are conform to AES75 and carried out with P9 processor and A42 amplifier. Values are scaled to 1m free field.

## Accessories

