

**Features**

- 2x 12" bass reflex design combined with 4"/2.5" coaxial compression driver
- Extended low frequency response at reduced power
- Quint Audio Quick Lock system on top and bottom
- Tool free mountable U-bracket
- 2x NLT4 on the rear
- 2x ergonomic handles, 1x on the left, 1x on the right
- Rubber feet for stability on the bottom
- All Quint Audio loudspeakers are designed for use in combination with Quint Audio processors & amplifiers
- All Quint Audio loudspeaker presets are matched in level and phase at the crossover frequency for easy mix & match
- Factory system presets available

**Applications**

- Top loudspeaker in combination with a subwoofer

**Construction**

- Birch plywood enclosure
- Durable hybrid coating, resistant to wear, impact, and weathering
- Klotz internal wiring
- Neutrik speakON® connectors
- Powder coated steel grille with acoustically transparent fabric on the back



<b>Model</b>	<b>T24</b>
Filter	2-channel DSP control
Loudspeaker components	2x12"/4"/2.5"
Impedance	5 Ohm
Peak SPL* / Freq. range (-6db)	143dB / 100Hz-20kHz
Max SPL* / Freq. range (-6db)	126dB / 100Hz-20kHz
Max SPL -10db / Freq. range (-6db)	116dB / 57Hz-20kHz
Max SPL -20db / Freq. range (-6db)	106dB / 47Hz-20kHz
Dispersion (HxV)	70° x 40°
Connections	2x 4-pole speakON
Weight	29kg
Size (WxHxD)	360 x 695 x 415mm

\* Measurements are conform to AES75 and carried out with P9 processor and A42 amplifier. Values are scaled to 1m free field.

**Accessories**