

U12 mk2

Universal point source for touring

Features

- 12" bass reflex design combined with 2.5" compression driver
- Extended low frequency response at reduced power
- Tool free mountable U-bracket
- Monitor angles 45 degrees and 75 degrees
- Mounting points for fixed installation
- 2x NL4 on the rear, 1x NL4 on the bottom
- 35mm Pole mount on bottom
- 1x ergonomic handles, 1x on the top
- M10 threads on left and right
- All Quint Audio loudspeakers are designed for use in combination with Quint Audio processors & amplifiers
- All Quint Audio loudspeaker presets are matched in level and phase at the crossover frequency for easy mix & match
- Factory system presets available



Applications

- Top loudspeaker in combination with a subwoofer
- Live monitoring

Construction

- Birch plywood enclosure
- Durable hybrid coating, resistant to wear, impact, and weathering
- Neutrik speakON® connectors
- Powder coated steel grille with acoustically transparent fabric on the front

| | |
|------------------------------------|-----------------------|
| Model | U12 mk2 |
| Filter | 1-channel DSP control |
| Loudspeaker components | 12"/2.5" |
| Impedance | 8 Ohm |
| Peak SPL* / Freq. range (-6db) | 137.5dB / 100Hz-20kHz |
| Max SPL* / Freq. range (-6db) | 118.5dB / 100Hz-20kHz |
| Max SPL -10db / Freq. range (-6db) | 108.5dB / 39Hz-20kHz |
| Max SPL -20db / Freq. range (-6db) | 98.5dB / 35Hz-20kHz |
| Dispersion (HxV) | 80° x 50° |
| Connections | 3x 4-pole speakON |
| Weight | 20kg |
| Size (WxHxD) | 360 x 610 x 340mm |

* Measurements are conform to AES75 and carried out with P9 processor and A42 amplifier. Values are scaled to 1m free field.

Accessories

