

U15

Universal full range point source for touring

Features

- 15" bass reflex design combined with 2.5" compression driver
- Maintained low frequency performance at full power
- Tool free mountable U-bracket
- Monitor angles 45 degrees and 70 degrees
- Mounting points for fixed installation
- 2x NL4 on the rear, 1x NL4 on the bottom
- 35mm-pole mount on bottom
- 1x ergonomic handles, 1x on the top
- M10 threads on left and right
- All Quint Audio loudspeakers are designed for use in combination with Quint Audio processors & amplifiers
- All Quint Audio loudspeaker presets are matched in level and phase at the crossover frequency for easy mix & match
- Factory system presets available



Applications

- Top loudspeaker in combination with a subwoofer
- Live monitoring

Construction

- Birch plywood enclosure
- Durable hybrid coating, resistant to wear, impact, and weathering
- Neutrik speakON® connectors
- Powder coated steel grille with acoustically transparent fabric on the front

Model	U15
Filter	1-channel DSP control
Loudspeaker components	15"/2.5"
Impedance	8 Ohm
Peak SPL* / Freq. range (-6db)	137dB / 41Hz-20kHz
Max SPL* / Freq. range (-6db)	120dB / 41Hz-20kHz
Max SPL -10db / Freq. range (-6db)	N/A
Max SPL -20db / Freq. range (-6db)	N/A
Dispersion (HxV)	60° x 50°
Connections	3x 4-pole speakON
Weight	23kg
Size (WxHxD)	435 x 740 x 410mm

* Measurements are conform to AES75 and carried out with P9 processor and A42 amplifier. Values are scaled to 1m free field.

Accessories

