

Features

- 6.5" bass reflex design combined with 1.7" compression driver
- Extended low frequency response at reduced power
- Tool free mountable U-bracket
- Monitor angles 50 degrees and 70 degrees
- Mounting points for fixed installation
- 2x NL4 on the rear
- M10 Thread for pole adapter
- 1x ergonomic handles, 1x on the back
- M10 Thread on bottom, M6 thread on top, M10 threads on left and right
- All Quint Audio loudspeakers are designed for use in combination with Quint Audio processors & amplifiers
- All Quint Audio loudspeaker presets are matched in level and phase at the crossover frequency for easy mix & match
- Factory system presets available



Applications

- Top loudspeaker in combination with a subwoofer
- Live monitoring

Construction

- Birch plywood enclosure
- Durable hybrid coating, resistant to wear, impact, and weathering
- Neutrik speakON® connectors
- Powder coated steel grille with acoustically transparent fabric on the front

Model	U6
Filter	1-channel DSP control
Loudspeaker components	6.5"/1.7"
Impedance	8 Ohm
Peak SPL* / Freq. range (-6db)	121.5dB / 100Hz-19kHz
Max SPL* / Freq. range (-6db)	109dB / 100Hz-19kHz
Max SPL -10db / Freq. range (-6db)	99dB / 60Hz-19kHz
Max SPL -20db / Freq. range (-6db)	N/A
Dispersion (HxV)	90° x 50°
Connections	2x 4-pole speakON
Weight	9kg
Size (WxHxD)	200 x 390 x 190mm

* Measurements are conform to AES75 and carried out with P9 processor and A42 amplifier. Values are scaled to 1m free field.


Accessories




U6-V1



U6-H1



U6-F1



U6-F1

