

B16C

Compact cardioid sub for touring & installation

Features

- 15"/12" bass reflex design
- Maintained low frequency performance at full power
- Noise suppression outside the sound field
- Stackable in omni & cardioid setup
- Mounting points for fixed installation
- 2x NLT4 2x NL8 on the rear
- M20 pole mount on top
- 2x ergonomic handles, 1x on the left, 1x on the right
- Rubber feet for stability on the bottom
- Optional front lid
- Transport wheels mountable on rear and on optional front lid
- Truck size cabinet for efficient transportation
- All Quint Audio loudspeakers are designed for use in combination with Quint Audio processors & amplifiers
- All Quint Audio loudspeaker presets are matched in level and phase at the crossover frequency for easy mix & match
- Factory system presets available


Applications

- Subwoofer for compact to medium systems
- Ground stacked subwoofer system
- Horizontal subwoofer array


Construction

- Birch plywood enclosure
- Durable hybrid coating, resistant to wear, impact, and weathering
- Klotz internal wiring
- Neutrik speakON® connectors
- Powder coated steel grilles with acoustically transparent fabric on the back


Accessories



B18-K1



C15-E1



C15-E2



Model	B16C
Filter	2-channel DSP control
Loudspeaker components	15"/12"
Impedance	4 Ohm
Peak SPL* / Freq. range (-6db)	137dB / 33Hz-100Hz
Max SPL* / Freq. range (-6db)	125dB / 33Hz-100Hz
Max SPL -10db / Freq. range (-6db)	N/A
Max SPL -20db / Freq. range (-6db)	N/A
Dispersion (HxV)	Cardioid
Connections	2x 8-pole speakON 2x 4-pole speakON
Weight	44kg
Size (WxHxD)	580 x 455 x 680mm

* Measurements are conform to AES75 and carried out with P9 processor and A42 amplifier. Values are scaled to 1m half space.

