

Features

- 2x 21" double chamber bass reflex design
- Maintained low frequency performance at full power
- Mounting points for fixed installation
- 2x NLT4 on the rear
- Rubber feet for stability on the bottom (and side)
- Truck size cabinet for efficient transportation
- All Quint Audio loudspeakers are designed for use in combination with Quint Audio processors & amplifiers
- All Quint Audio loudspeaker presets are matched in level and phase at the crossover frequency for easy mix & match
- Factory system presets available

Applications

- Subwoofer for medium to large systems
- Cardioid setup
- Ground stacked subwoofer system
- Horizontal subwoofer array

Construction

- Birch plywood enclosure
- Durable hybrid coating, resistant to wear, impact, and weathering
- Klotz internal wiring
- Neutrik speakON® connectors
- Powder coated steel grille with acoustically transparent fabric on the back



Model	C42
Filter	1-channel DSP control
Loudspeaker components	2x21"
Impedance	4 Ohm
Peak SPL* / Freq. range (-6db)	146dB / 31Hz-100Hz
Max SPL* / Freq. range (-6db)	135dB / 31Hz-100Hz
Max SPL -10db / Freq. range (-6db)	N/A
Max SPL -20db / Freq. range (-6db)	N/A
Dispersion (HxV)	Omni
Connections	3x 4-pole speakON
Weight	124kg
Size (WxHxD)	1180 x 590 x 1000mm

* Measurements are conform to AES75 and carried out with P9 processor and A42 amplifier. Values are scaled to 1m half space.

Accessories

