

Features

- 21" bass reflex design
- Maintained low frequency performance at full power
- 2x NLT4 2x NL8 on the rear
- M20 pole mount on top and optional on sides
- 4x ergonomic handles, 2x on the top, 2x on the bottom
- Rubber feet for stability on the bottom and optional on sides
- Optional front lid
- Transport wheels mountable on rear
- Truck size cabinet for efficient transportation
- All Quint Audio loudspeakers are designed for use in combination with Quint Audio processors & amplifiers
- All Quint Audio loudspeaker presets are matched in level and phase at the crossover frequency for easy mix & match
- Factory system presets available

Applications

- Studio monitoring
- Subwoofer for medium to large systems
- Ground stacked subwoofer system
- Horizontal subwoofer array

Construction

- Birch plywood enclosure
- Durable hybrid coating, resistant to wear, impact, and weathering
- Klotz internal wiring
- Neutrik speakON® connectors
- Powder coated steel grille with acoustically transparent fabric on the front



Model	Rsub
Filter	1-channel DSP control
Loudspeaker components	21"
Impedance	4 Ohm
Peak SPL* / Freq. range (-6db)	136dB / 19Hz-100Hz
Max SPL* / Freq. range (-6db)	125.5dB / 19Hz-100Hz
Max SPL -10db / Freq. range (-6db)	N/A
Max SPL -20db / Freq. range (-6db)	N/A
Dispersion (HxV)	Omni
Connections	2x 8-pole speakON
Weight	2x 4-pole speakON
Size (WxHxD)	89kg
	580 x 1165 x 680mm

* Measurements are conform to AES75 and carried out with P9 processor and A4 amplifier. Values are scaled to 1m fhalf space.

Accessories

