

V36

High performance active directivity control full range line array module for touring

Features

- 2x 18"/2x 15" bass reflex 4x 8" closed box design combined with 2x 4"/2.5" coaxial compression driver
- Symmetrical design
- Maintained low frequency performance at full power
- Full range constant directivity
- Noise suppression outside the sound field
- Rigging system for use with downfill L-series modules
- 2x NL8 on the rear
- All Quint Audio loudspeakers are designed for use in combination with Quint Audio processors & amplifiers
- All Quint Audio loudspeaker presets are matched in level and phase at the crossover frequency for easy mix & match
- Factory system presets available

Applications

- Full range line source

Construction



- Birch plywood enclosure
- Durable hybrid coating, resistant to wear, impact, and weathering
- Klotz internal wiring
- Neutrik speakON® connectors
- Powder coated steel grilles with acoustically transparent fabric on the back



Model	V36
Filter	4-channel DSP control
Loudspeaker components	2x18"/2x15"/4x8"/2x4"/2x2.5"
Impedance	4 Ohm
Peak SPL* / Freq. range (-6db)	148dB / 33Hz-20kHz
Max SPL* / Freq. range (-6db)	130dB / 33Hz-20kHz
Max SPL -10db / Freq. range (-6db)	N/A
Max SPL -20db / Freq. range (-6db)	N/A
Dispersion (HxV)	80° x 10°
Connections	2x 8-pole speakON
Weight	167kg
Size (WxHxD)	1180 x 540 x 1045mm

* Measurements are conform to AES75 and carried out with P9 processor and A42 amplifier. Values are scaled to 1m free field.

Accessories



Flying pin 2

